

PRODUCT FILE
1610-F2

| GENERAL SPECIFICATIONS(mm) |
|--|
| Lens thickness: 0.5 mm |
| PD: 68 mm |
| Lens Base: 8 curve |
| Weight: 28gm |
| Lens size vertical: 44.5 mm |
| Lens size diagonal: 60.5 mm |
| Bridge: 12 mm |
| Temple length(lens-tip): 162 mm |
| Overall Width(hinge-hinge): 140 mm |
| Closest point between lens: 15 mm |
| Closest point between temple tips: 86 +/- 3 mm |



| COMPONENT | MATERIAL | FEATURES |
|------------------|-----------------|-------------------------------|
| Lens | Stainless Steel | wire mesh |
| Frame | Nylon | Dual lens design |
| Lens Carrier | Nylon | Interchangeable lens carrier |
| Nose piece | N/A | Integral to the frame |
| Temple tip | NON-P PVC | Soft tips for comfort |
| Temple | PC | Straight side style, flexible |
| Screw | Stainless Steel | Standard screw hinge |

FRAME OPTIONS

| | |
|---------------|---------|
| Frame colors: | Various |
|---------------|---------|

SPECIAL FEATURES

- * Interchangeable lens system allows quick lens installation.
- * Suitable for different working environments and weather conditions.
- * PC temple with non-slip soft tip is comfortable, durable and resilient.
- * Where used:
 - Forestry
 - Mining
 - Manual can cutting and similar activities, any environment where there is danger of eye injury from small or medium size particles and where fogging is a major problem
 - Dirty working environments, where require constant cleaning
 - Humid working environments, where easily cause fogging and scratching
 - Does not provide protection against fine dust or splash